



## Tech Specs

<b>Form Factor/Height</b>	<b>1U Rack</b>
<b>Processor (max)/Cache (max)</b>	Xeon Silver 4110 (8C 2.1GHz 11MB Cache/85W)
<b>Memory</b>	16 GG DDR4 – 2400 MHz
<b>Drive Bays</b>	1.8 Sas
<b>HBA/RAID Support</b>	Software RAID std. (up to 8 ports); opt. hardware RAID (up to 8 ports) with flash cache; up to 8-port HBAs
<b>Security and Availability Features</b>	TPM 1.2/2.0; PFA; HS/redundant drives and PSUs; operating temp up to 45°C (with limitations); front-access diagnostics via dedicated USB port
<b>Network Interface</b>	5x 1GbE ports + 1x dedicated 1GbE management port (std); optional modular LOM supports 2x 1GbE Base-T or 2x 10GbE with Base-T or SFP+
<b>Power</b>	2x hot-swap/redundant (Energy Star 2.1): 550W/750W 80 PLUS Platinum; or 750W 80 PLUS Titanium
<b>Systems Management</b>	XClarity Controller embedded management, XClarity Administrator centralized infrastructure delivery, XClarity Integrator plugins, and XClarity Energy Manager centralized server power management
<b>Operating Systems Supported</b>	Server 2008 R2 Or Server 2012 R2