



## Tech Specs

<b>Form Factor/Height</b>	Single-socket entry 4U tower ; 25 Liter
<b>Processor (Max) Cache (Max)</b>	Intel Celeron G4620 3.7GHz
<b>Memory DIMMS</b>	4 Giga 2400MHz ECC UDIMMs
<b>Media Bays</b>	Two without a backup drive or one with a backup drive. Support for DVD-ROM or DVD-RW.
<b>Disk Bays</b>	1 Terra Sata 7200 Rpm
<b>Power Supply (Std/Max)</b>	1/1; 250W 80 PLUS Bronze or 400W 80 PLUS Platinum (non-hot-swap)
<b>Network Interface</b>	4 Port
<b>Expansion Slots</b>	<ul style="list-style-type: none"> <li>• 4 PCIe 3.0 slots: x16/x16; x16/x4; x1/x1; x1/x1 (open end)</li> <li>• 1 x PCIe 3.0: HL/FH: x16/x4</li> <li>• 1 x PCIe 3.0: HL/FH: x1</li> </ul>
<b>Ports</b>	8x USB 3.0 (2 front; 6 rear), 1x RJ-45 Ethernet, 1x serial (COM); 1x VGA (plus 1x DP), 3x audio (mic/lineout/line in), 1 x DisplayPort, 1 x RJ-45, 1 x serial (9-pin), 3 x audio (line-in, line-out, microphone)
<b>Cooling</b>	3 x fans, non-hot swap
<b>Operating Systems Supported</b>	Server 2008 R2 \Server 2012 R2
<b>Dimensions (W x H x D) &amp; Weight</b>	174.75mm (W) x 374.90mm (H) x 430.78mm (D)/6.88 inches (W) x 14.76 inches (H) x 16.96 inches (D); Max. 12,5kg/27.6.lbs